

Part Number: 6899

6899 Thin Client for VDI Enterprise Class

The 6899 is the next generation Thin Client. This Series has all the features of a traditional PC, but was built with a future proof design and high energy efficiency, resulting in the use of less power and will reduce management and overall power costs.

The 6899 has been designed for businesses of all sizes. This Thin Client has dual DVI video ports, optional legacy ports and a PCIe expansion slot. It uses the AMD Embedded G-Series Dual Core Processor to achieve a high performance workstation. The 6899 Thin Client is an excellent solution for companies looking to shift their business to a server-based environment.

10ZiG's management utility offers simple solutions to troubleshooting, OS updates and software installs, ultimately cutting out the need for additional IT administration, thus lowering the total cost of ownership.

▶ NoTouch OS 2.38	▶ Centralized Management
▶ Supports High End Graphics	▶ Embedded Lockdown Manager (WE8)
▶ Dual/Quad Monitor Capabilities	▶ Legacy Serial/Parallel Ports Available
▶ Internal Wireless (Optional)	▶ Support for USB 2.0 and USB 3.0



*Featuring Support for Virtual Bridges & Quest.



Americas
EMEA
APAC

P: 866-865-5250
P: +44 (0) 116 214 8650
P: 1300 768 799

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au

W: www.10ZiG.com
W: www.10ZiG.eu
W: www.10ZiG.com.au

Learn More

6899 Thin Client for VDI

System	
Management	10ZiG NoTouch Management Utility
Form Factor	Micro Tower
Processor	Dual Core 1.65GHz
Chipset	AMD Embedded G-Series T56E/T56N
Dimensions	
Device	2.2"(W) x 9"(H) x 8.2"(D)
Weight	3.7 lbs
Connections	
Ports	USB x 6 (USB 2.0 x 4, USB 3.0 x 2), Serial Port x 1, PS2 x 1 - (Optional Parallel & additional Serial Port via PCIe Card)
Video/Audio	DVI x 2, Line-Out x 1, Internal Speaker x 1
Networking	
Wireless	Optional internal wireless a/b/g/n
Ethernet	RJ-45 10/100/1000 Base-T
Environmental	
Operating Temp.	32-95F (0-25C), 20-80% non-condensing humidity
Power	16 Watt Consumption, 48 Watt, DC-12V/4A External Power Adapter



SPECIFICATIONS

1. Power Button (LED inside)
2. HDD Led
3. Network Light
4. Mic In
5. Audio Out
6. Smart Card Reader (option)
7. USB 2.0 Ports (x2)
8. Speaker
9. PS/2 Port
10. USB 3.0 Ports (x2)
11. USB 2.0 Ports (x2)
12. Ethernet 10/100/1000
13. Spare PCI Expansion Slot
14. DVI-D Socket
15. DVI-I Socket
16. Serial Port
17. DC Jack
18. Kensington Lock

WARRANTY: All Thin Clients include a 3-Year Advanced Exchange Warranty

6899

Operating System 10ZiG NoTouch (Linux)

Memory

RAM	MIN: 1GB MAX: 2GB
Storage	MIN: 1GB MAX: 2GB

Software

Software Applications	Firefox, Citrix Receiver, RDP, Sun JVM, VNC
-----------------------	---

VDI Connection Brokers Supported

Citrix XenDesktop & VDI-In-a-Box w/ HDX, VMware Horizon View w/ PCoIP, 2X, Quest vWorkspace